

WARRANTLY LETTER OF POLYESTER TOP COAT PAINTED PRODUCT

DATE: 2016-10-19

Dear Customers,

FAREAST STEEL INTERNATIONAL LIMITED warrants that the Polyester Top Coat Painted products resist to the normal atmospheric and chemical exposure according to the table given below. Only "Article 1" is valid if the products used at the further south from 30°north latitude.

Corrosion resulting from physical damage or cut edges is excluded from any warranty.

Article	Property	Structure	Distance From Sea (m)	
			1000+	0-1000
1	Flaking	Non-Vertical Applications	8 years, <10%	No Guarantee
		Vertical Applications	10 years, <10%	No Guarantee
2	Color Change (CIElab, △E)	Non-Vertical Applications	8 years, △E≤10 (For White	No Guarantee
			Colors, 8 years, △E≤8)	
		Vertical Applications	10 years, △E≤10 (For White	No Guarantee
			Colors, 8 years, △E≤8)	

This warranty is valid only the following conditions are met:

- ·Top coat paint should be applied on compatible primer. (Top coat at least 20um + Primer at least 5 um)
- · Products should not get damaged (mechanical and chemical) while painted sheets being formed.
- · Products should be safe from any scratches, the occurance of hole, impact, spunk, butts, etc.
- · Treated panels should not get damaged in the storage, transportation and installation steps.
- · Cut edges and holes of the treated panels should be protected with the correct protection.
- Building maintenance should be carried out including regular cleaning with suitable products and procedures.
- Building should not be exposed to natural disasters (earthquake, storm, lightning, flood, fire, etc) and aggressive chemical environment (industrial waste, ammonia, chlorine, salt, acid rain, etc.)

Best Regards,

FAREAST STEEL INTERNATIONAL LIMITED

